

Style and Design



Strip parquet



- 1 7 coats of Rangifer® varnish
- 2 hardwood top layer
- 3 pine middle layer
- 4 bottom layer of softwood veneer



Why Grabo **Viking** parquet?

Because it merges the vibrating energy of the wood with the unique surface design, creating a style for you.

Because it is...

- › durable
- › reliable
- › easy to install
- › environment-friendly

Rangifer®



30 YEAR GUARANTY

Oak



OAK, BRUSHED

OAK, BRUSHED LIGHT



OAK, BRUSHED DARK

Past and present



Ash



ASH, BRUSHED



ASH, BRUSHED LIGHT

ASH, BRUSHED DARK



Lights and shadows

Merbau



MERBAU, BRUSHED

MERBAU, BRUSHED LIGHT



MERBAU, BRUSHED DARK

Space and shape



Wenge





WENCE, BRUSHED

WENCE, BRUSHED LIGHT



Black and white

Maintenance and Cleaning

General notes:

Your ready-to-install parquet floor is protected from the penetration of dust and dirt by several coating layers. Excellent surface finish accounts for a long service life of your parquet floor that can be further extended by appropriate maintenance and care. Simple care helps to preserve the value and beauty of your parquet

Indoor climate conditions:

Just like its owners, the parquet floor “feels” best at approx. 50–60% relative air humidity with a room temperature of 18–20 °C. It is important to keep the air humidity constant. Healthy humidity levels can be achieved by vaporisers placed on top of the heaters, by aquariums and green plants, as well as by using electric air humidifiers for larger premises. The indoor climate conditions can be measured by simple instruments like hygrometer and thermometer. Too low air humidity values can lead to increased joint and expansion gaps.

Use the following precautions to prevent surface damage to you parquet floor:

- Use felt pads on table and chair legs.
- Use protective mats with your office chairs and other mobile furniture.
- A doormat at the entrance will protect the parquet floor from scratches (the dust and sand on your shoe soles work as sandpaper for your parquet surface).

Daily cleaning

For optimal effect, we recommend you to use a felt or soft broom vacuum cleaner to remove the dust and engrained or built-up dirt from the structured surface of your parquet floor. When required, continue the cleaning by damp mopping using a parquet care product designed specifically for cleaning and maintenance of your floor. Strips and stains caused by shoes can be cleaned with parquet stain remover and a damp fiber pad.

Refinishing

Your parquet is usually delivered with a ready-to-use surface finish; therefore, no additional finishing is required upon installation. However, to repair small damages and the wear-and-tear effects after a longer period of use, the surface can be sanded and re-finished with varnish, wax or oil. Depending on the intensity of sanding, the surface structure will regain its original shine. Surface repair should be performed with professional tools, by qualified professionals.

In case of further questions, please, contact your dealer or a flooring specialist, or feel free to write directly to us at Craboplast.

Technical Specifications:

	varnished
OAK BRUSHED	matt
	matt light
	matt dark
ASH BRUSHED	matt
	matt light
	matt dark
MERBAU BRUSHED	matt
	matt light
	matt dark
WENGE BRUSHED	matt
	matt light

Brinell hardness			
Oak	▶	35	Merbau ▶ 34
Ash	▶	38	Wenge ▶ 53

Technical Specifications			
	2250x190x13.5 mm		6
	cca 3.6 mm		2.565 m ²
	7.5 kg/m ²		102.6 m ²



www.realwood.eu

BW12-01

Member of
FEP



Graboplast Floor Covering Manufacturers Ltd.
H-9023 Győr, Fehérvári út 16/B HUNGARY
Tel.: (36) 96 506-154, E-mail: mail@graboplast.hu
www.graboplast.hu

